

Remote Water Sensing Pod (Add On)

Your Home, Only Smarter

The DCH-S163 Remote Water Sensing Pod helps you keep your home dry with app notifications and audio/visual alerts when paired with the DCH-S162

DCH-S163

- Get audio alerts from Google Assistant
- Audible alerts via DCH-S162 when water is detected
- Strobe LED flashes via DCH-S162 when water is detected
- Battery-powered for unrestricted placement
- IP65 dust & water-resistant design
- Metal probes for water detection
- Rich Notifications let you take action right from your lock screen
- mydlink™ app support¹













Water Detection Alerts

Push notification when water is detected²



Metal Probes

4 metal probes for water detection



Extreme Range

Long-distance wireless connection (up to 1,000 ft)



LED Strobe Alert

Visual alerts via DCH-S162 when water is detected



IP65 Design

IP65 dust & Water-resistant design



Intuitive App

The mydlink app lets you manage your device anytime, anywhere



100 dB Siren

Audible alerts via DCH-S162 when water is detected



Smart Home Compatible

Works with mydlink Smart Home devices and Google Assistant

Device Management


| General | |
|---------------------|--|
| Device Interfaces | Reset buttonSub-GHz wireless |
| Connectivity | 915 MHz bandRange: 300 ft (indoor) / 1,000 ft (open area) |
| LED | • Status |
| Wireless Encryption | AES 128-bit encryption |

| Functionality | | |
|--------------------|---|---|
| Supported Features | • | Battery powered Long battery life Long range connection 4 metal probes for water detection |
| | • | IP65 dust & water-resistant design Push notifications w/ quick actions buttons to call up to 2 designated contact numbers and turn off the siren Google Assistant |

mydlink app

| Physical | |
|-------------------|--|
| Dimensions | • 66.4 x 66.4 x 20.6 mm |
| Weight | • 69 grams |
| Power | AAA battery x 2 (pre-installed) Battery Life: over 5 years standby time³ |
| Power Consumption | Standby: <= 18 uWActive: <= 66 uW |
| Temperature | Operating: 0 to 40 °C (32 to 104 °F) Storage: -20 to 70 °C (-4 to 158 °F) |
| Humidity | Operating: 10% to 90% non-condensingStorage: 5% to 95% non-condensing |
| Certifications | FCCICRoHS |







¹ Please visit www.dlink.com for more information on mydlink products that support Smart Home functionality.

² This product is intended solely to help reduce damage caused by a water leak. D-Link disclaims all liability for any water damage that occurs as result of the failure of this product to properly function.

³ 5 year battery life based on triggering one time per week