

DCS-2100G Firmware Release Note

Firmware: 1.03

Hardware: A1

Date: Sep 28, 2005

Checksum: 0017EA54

Problems Resolved:

1. The WEB page can't show full screen when PC screen resolution in 800*600.
2. In Ad hoc mode, the channel select item will be disabled after entering the setting page next time.

Enhancements:

1. Add snapshot size in Application page.
2. Show number of current users on line.
3. Add java script to verify IP address format in fields of IP address, subnet mask, default router, primary DNS, and secondary DNS.
4. Http port should only allow numeral input.
5. Creating new folder in ftp remote folder when uploading images.
6. SSID can allow space character.
7. Grey out the data encryption section when it is disabled.
8. Encryption key – fill 0 in HEX mode or space in ASCII mode if the key field is empty.
9. Wireless module hardware limitation issue, so modify the below item:
 - In authentication options, "AUTO" mode is removed.
 - In ad-hoc mode, it only shows "Both" mode in authentication options.

Firmware: 1.02

Hardware: A1

Date: Apr 18, 2005

Checksum: 0017B614

Problems Resolved:

In v1.00, it requires users to set the same 4 WEP key of DCS-2100G as those in router/AP, and the 4 WEP keys should be filled-in to activate this function. These are not convenient for users and inconsistent with other D-Link wireless products.

V1.02 resolved this bug and added LED on/off function which is supported in another

DCS series product.

Firmware: IP3136-DLNK-0100f (1.00)

Hardware: A1

Date: December 17, 2004

Checksum: 0016E094

Initial release
