

DCS-5300



**PAN,
TILT,
AND
ZOOM**

- CCD Sensor for Superior Quality Video
- Built-in Microphone for Audio Monitoring and Recording
- High Quality MPEG-4 Short Header Mode Compression
- Built-in Motion Detection & E-mail Notification
- A/V Output Enables Connection to TV & External Speakers

**10/100
Mbps
SPEED**

**CCD
SENSOR**

**UPnP
Universal Plug-&-Play
DDNS**

**WEB
BASED
CONFIGURATION**

**FREE
24/7
TECH
SUPPORT
(USA ONLY)**

SECURICAM Network *10/100 Fast Ethernet Pan, Tilt, & Zoom* **Internet Camera**

Remotely watch and listen with the D-Link SECURICAM Network DCS-5300 Internet Camera. The DCS-5300 Internet Camera is a full-featured surveillance system that connects to an Ethernet or Fast Ethernet connection to provide high quality video and audio over the Intranet or the Internet.

The DCS-5300 Internet Camera differs from a conventional PC Camera because the DCS-5300 is a stand-alone device with a built-in CPU and Web server that allows you to access your camera using Internet Explorer 5.X or above from anywhere in the world.

The D-Link DCS-5300 also has a pan, tilt, and digital zoom function that can be controlled from the Web interface or from the included remote control. Auto pan mode enables the camera to move 270 degrees horizontally and the Patrol mode cycles through up to 20 preset positions. The speed of either pan or tilt can be adjusted to your preference. The 4x digital zoom lens enables the camera to obtain a closer view.

The D-Link DCS-5300 comes with a CCD sensor that provides a sharp and clear image with life-like color representation. The sensor is a CCD sensor with resolution of 380 TV lines. The built-in microphone adds sound that accompanies the video. Altogether, you can record streaming video with

sound that utilizes high quality MPEG4 Short Header Mode Compression to your hard drive, enable motion detection, and set up automated e-mail alert notification.

A powerful surveillance software is included to enhance the monitoring and management of your DCS-5300. The bundled surveillance software further enhances the security features of the DCS-5300, allowing you to archive streaming video and audio straight to your hard drive, playback video, monitor as many as 16 cameras on a single screen, and set up motion detection to trigger automatic recording.

By signing up with one of the many Dynamic DNS services, you can assign an easy-to-remember name and domain (e.g. www.mycamera.myddns.com). This allows you to remotely access your camera without having to remember the IP address, even if it has been changed by your Internet Service Provider.

The DCS-5300 is a Price/Performance breakthrough, feature rich solution capable of meeting demanding security and home/office monitoring needs. Secure your site with the D-Link Securicam DCS-5300 Internet Camera.

SECURICAM Network 10/100 Fast Ethernet Pan, Tilt, & Zoom **Internet Camera**

SPECIFICATIONS

Power Input

- External Power Supply
- 12VDC 1.5A

Remote Management

Configuration and system log can be accessed via Web browser and FTP application remotely

Networking Protocol

TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS and DHCP

Network Application

- DDNS support with several popular DDNS servers
- UPnP support
- SMTP client
- FTP client
- FTP server
- HTTP server

Ethernet

10BaseT or 100BaseT Fast Ethernet

Video Algorithm Supported

H.263+ (MPEG4 Short Header Mode)

Features

- Built-in Motion Detection
- MPEG4 short header mode compression for streaming video
- JPEG compression for still image

Audio

- 24Kbps
- Built-in omni-directional microphone

Video Resolution

- Up to 30fps at 160x120
- Up to 30fps at 320x240

Camera Specification

- 1/4 inch color CCD sensor
- AGC/AWB
- Electronic shutter: 1/60~1/15000 sec.
- Fixed focus glass lens, F2.0, 1 LUX

General I/O

- 1 Opto-isolated sensor input (max. 12VDC 50mA)
- 1 relay output (max. 24VDC 1A, 125VAC 0.5A)

Pan, Tilt, & Zoom Control

- Auto pan and auto patrol mode with preconfigured stops
- Pan: Range 270 degrees
- Tilt: Range 90 degrees
- 4x Digital Zoom

Ports

- 10/100 Mbps Fast Ethernet
- Audio/Video output
- External microphone input
- External I/O

Security

- Administrator and user group protected
- Password authentication

Viewing System Requirement Protocol

ActiveX

Operating System

Microsoft Windows® XP, 2000, Me or 98SE

Browser

Internet Explorer 5.x or above

LEDs

- 2 Status indicators.
 - (1) Power
 - (2) POST, connection, and heartbeat

Dimension

4.0" L x 4.1" W x 4.4 "H

Weight

12.2 oz. (0.751lb)

Warranty

1 Year



Pan, Tilt, & Zoom Surveillance for Home/Office

Use of audio or video equipment for recording the image or voice of a person without their knowledge and consent is prohibited in certain states or jurisdictions. Nothing herein represents a warranty or representation that the D-Link product provided herein is suitable for the end-user's intended use under the applicable laws of his or her state. D-Link disclaims any liability whatsoever for any end-user use of the D-Link product which fails to comply applicable state, local or federal laws.



D-Link Systems, Inc. 17595 Mt. Herrmann Fountain Valley CA92708-4160 www.dlink.com
©Copyright D-Link Systems, Inc. 2003. All rights reserved. D-Link® is a registered trademark of D-Link Systems, Inc.
Other trademarks or registered trademarks are the property of their respective manufacturers or owners.
Price and specifications are subject to changes without notice. See inside package for warranty details.
* 24/7 Tech Support is available only in USA.

D-Link®
Building Networks for People