D-Link Building Networks for People DP-311U

Share Your USB Printer Wirelessly

- Easily set up with Web Browser or Windows Configuration Program
- Ethernet Port and One USB Port for Connection to Compatible Printers
- Compact Size for Easy Placement
- Built in 802.11b Compliant Wireless











Air Wireless Network 2.4GHz Wireless Print Server

D-Link, the industry pioneer in networking, continues to offer innovative Ethernet products. The D- Link DP-311U is a wireless print server with one USB port. With its high-speed USB port, the DP-311U allows those on your network to access and share a USB printer wirelessly no matter where they reside on the network.

The DP-311U is equipped with one USB version 1.1 port for seamless connection to most printers available on the market today. The DP-311U also supports all major network Operating Systems and protocols.

The DP-311U is an 802.11b compliant wireless Print Server that supports both infrastructure or

Ad-hoc wireless modes. With the DP-311U you have the ability and convenience of sharing a printer beyond the wired network.

The DP-311U is also easily configurable using a Web Browser or Windows based configuration program. Using Web Browsers on a PC connected to the network, configuration is simple and straightforward with the familiar D-Link interface. PS Admin, a Windows-based configuration program can also be used to configure the DP-311U.

The DP-311U Wireless Print Server is the ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing.

Air™Wireless Network

2.4GHz Wireless

Print Server

SPECIFICATIONS

Standards

- · IEEE 802.2
- · IEEE 802.3
- · IEEE 802.3u
- IEEE 802.11b
- · USB 1.1

Port

- · 10/100 Mbps Fast Ethernet
- · USB 1.1 Port

Signal Rates¹ With Automatic Fallback

- 11Mbps
- 2 Mbps
- 5.5Mbps
- 1 Mbps

Transport Protocols

- · TCP/IP
- · NetBEUI
- · AppleTalk / EtherTalk

TCP/IP Protocols Supported

- · BOOTP
- · SNMP
- · Telnet
- · TFTP
- · FTP
- · LPD
- · RARP
- · DHCP

Management

SNMP

MIBs

MIB-II (RFC 1213)

Diagnostic LEDs

- · Power
- · Link/Activity
- · USB
- · WLAN

Power Input

- · External Power Supply
- · DC 5V, 2.5A

Dimensions

- $\cdot L = 3.54" (90mm)$
- \cdot W = 3.19" (81mm)
- \cdot H = 1.57" (40mm)

Weight

0.32 lbs (147g)

Operating Temperature 0°C to 50°C

Storage Temperature

-25°C to 55°C

Humidity

- · 5% to 95%
- · non-condensing

Warranty

1 Year

¹ Maximum wireless signal rate based on IEEE Standard 802.11b specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead lower actual data throughput rate









The D-Link DP-311U is a wireless Print Server with 1 USB port. The DP-311U will let you share a USB printer amoung computers connected to a home or small office network.



