

DP-G310



- Easily Set Up with Web Browser or Windows Configuration Program
- Ethernet Port and One USB Port for Connection to Compatible Printers
- Compact Size for Easy Placement
- Built-In 802.11g Wireless

AirPlus[®] **G** Wireless G **USB Print Server**

D-Link, the industry pioneer in networking, continues to offer innovative wireless products. The D-Link DP-G310 is a Wireless Print Server with one USB port. With its high-speed USB port, the DP-G310 allows those on your network to access and share a USB printer wirelessly no matter where they reside on the network.

The DP-G310 is equipped with one USB version 2.0 port for seamless connection to most printers available on the market today. The DP-G310 supports TCP/IP, NetBEUI and Apple Talk/EtherTalk printing.

The DP-G310 is an 802.11g Wireless Print Server that supports both Infrastructure or Ad-Hoc wireless

modes. With the DP-G310, you have the ability and convenience of sharing a printer beyond the wired network.

The DP-G310 is also easily configurable using a Web browser or Windows-based configuration program. Using Web browsers on a PC connected to the network, configuration is simple and straightforward with the familiar D-Link interface. PS Admin, a Windows-based configuration program, can also be used to configure the DP-G310.

The DP-G310 Wireless Print Server is the ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing.

AirPlus[®] G

Wireless G

USB Print Server

DP-G310



The D-Link DP-G310 is a Wireless Print Server with one USB port. The DP-G310 will let you share a USB printer among computers connected to a home or small office network.

SPECIFICATIONS

Standards

- IEEE 802.2
- IEEE 802.3
- IEEE 802.3u
- IEEE 802.11g
- USB 2.0
- USB 1.1

Ports

- 10/100 Mbps Fast Ethernet
- USB 2.0 Port

Wireless Signal Rate¹

54Mbps

Transport Protocols

- TCP/IP
- NetBEUI
- AppleTalk / EtherTalk

TCP/IP Protocols

Supported

- BOOTP
- SNMP
- Telnet
- TFTP
- FTP
- LPD
- RARP
- DHCP

Management

SNMP

MIBs

MIB-II (RFC 1213)

Diagnostic LEDs

- Power
- Link/Activity
- USB
- WLAN

Power Input

- External Power Supply
- DC 5V, 2.5A

Dimensions

- L = 3.54" (90mm)
- W = 3.19" (81mm)
- H = 1.57" (40mm)

Weight

0.32 lbs (147g)

Operating Temperature

0°C to 50°C

Storage Temperature

-25°C to 55°C

Humidity

- 5% to 95%
- non-condensing

Warranty

3 Year

¹ Maximum wireless signal rate derived from IEEE Standard 802.11g specifications. Actual data throughput will vary. Network conditions and environmental factors, including volume of network traffic, building materials and construction, and network overhead, lower actual data throughput rate. Environmental factors will adversely affect wireless signal range.

All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein. Visit www.dlink.com for more details.

