



## FEATURES

### Wireless Connectivity

- + IEEE 802.11g/b Compatible

### Video Output Connectors

- + VGA
- + DVI-D

### Resolution

- + Up to XGA (1024x768)

### Multiple Presenter Support

- + Connect Up to 10 Presenters

### Access an Internet Connection

- + Allow Presenters to Connect to the Web<sup>1</sup>

### Compact Size

- + Small Form Factor for Easy Placement

### No CD Required

- + Software Installs Directly from the DPG-2100

## Wireless Presentation Gateway

### Overview

The D-Link Wireless Presentation Gateway (DPG-2100) allows presenters to wirelessly connect to a projector or monitor. Display presentations, applications, and images from several notebooks or desktops without connecting additional bulky wires. With just a few clicks you can begin your presentation in style and impress clients. Reduce the amount of downtime in meetings associated with multiple presenters and enjoy a more productive presentation experience.

### Use Your Existing Monitor or Projector

The Wireless Presentation Gateway includes both VGA and DVI-D outputs making it compatible with the majority of projectors and monitors on the market today.

### Wireless Connectivity

Based on the 802.11g wireless standard, the DPG-2100 is compatible with a wide range of wireless devices including legacy 802.11b wireless devices. This enables presenters to use their existing 802.11b wireless devices without having to incur additional costs from upgrading.

### Display What You Want

The Wireless Presentation Gateway can handle any file format that your projector or monitor can support, including files produced by Microsoft® Office applications such as PowerPoint®, Excel®, and Word®. With audio support, you can liven up presentations with sound by connecting speakers to your projector or monitor.

### Connect to the Internet

Allow presenters to access the Internet and integrate content from the Web into their presentations. Simply connect the DPG-2100 to an existing network via the Ethernet port and presenters will have Internet access<sup>1</sup>.

### Easy to Use

D-Link's management software installation process is simple. The software enables seamless delivery of presentations for multiple users by way of a simple Connect / Disconnect button.

Connect with confidence using the D-Link Wireless Presentation Gateway (DPG-2100) and enjoy a new and enhanced presentation experience.



## Wireless Presentation Gateway

### Technical Specifications

Standards	+ IEEE 802.11g + IEEE 802.11b
Protocol	TCP/IP
External Antenna Type	Single Detachable Reverse SMA
Resolution	Up to XGA (1024 x 768)
Color Quality	16-Bit
Device Interface	+ 15-pin VGA + DVI-D
LED	Power/Status
Device Management	Connection Management Utility
Operating Temperature	14°F to 122°F (-10°C to 50°C)
Operating Humidity	5% - 95% (Non-condensing)
Dimensions	+ Item (WxDxH): 6.6" x 3.8" x 1.0" + Packaging (WxDxH): 10.8" x 8.1" x 2.6"
Weight	+ Item: 0.9 lbs + Packaging: 1.9 lbs
Certifications	+ FCC Class B + CE
System Requirements	Computer with: + 900MHz Processor + 256MB Memory + Windows® XP SP2 or Windows 2000 SP4 + Internet Explorer 6 or Higher or Mozilla Firefox
Warranty	1-Year Limited <sup>2</sup>

<sup>1</sup> Additional hardware devices, software, or services may be required for access to an Internet connection.

<sup>2</sup> 1-Year Limited Warranty available only in the USA and Canada.

Latest documentation is available at <http://support.dlink.com>.

Product specifications, size and shape are subject to change without notice, and actual appearance may differ from that depicted herein.