
D-Link®



2-PORT USB 3.0 PCI EXPRESS CARD

Blazing Speeds – transfer files up to 10x faster than USB 2.0²



Instant Upgrade - just add it to your desktop's PCI Express Card slot to instantly add 2 USB 3.0 ports



Backward Compatible with USB 2.0 and 1.12 devices



SUPERSPEED USB 3.0 CAPABILITIES

Connect your PC to USB 3.0 devices to transfer data at blazing speeds of up to 5 Gbps¹ - up to 10 times faster than USB 2.0. You can back up your photos, music, and HD movies to an external storage device faster than ever before. SuperSpeed USB delivers maximum power efficiency to save the energy cost. You can also charge USB 3.0 devices faster using the DUB-1310.

PLUG AND PLAY CONNECTIVITY

Just run the Setup CD and then slide the DUB-1310 into an available PCI Express slot; it's that simple to add 2 USB 3.0 ports to your PC.

CONNECT ALL YOUR PERIPHERALS

Backward compatibility with USB 2.0 and USB 1.12 means that you can connect any USB device to the DUB-1310. If you need more ports, you can connect additional USB hubs to support up to 127 devices¹.


USB DUB-1310

WHAT THIS PRODUCT DOES The D-Link 2-Port USB 3.0 PCI Express Card (DUB-1310) adds 2 USB 3.0 ports to your PC, allowing you to connect USB devices such as external storage, digital cameras, printers, and more. Providing data rates of up to 5Gbps - 10 times faster than USB 2.01. You can transfer your photos, music, and HD movies to a USB 3.0 external

storage device faster than ever before.

DUB-1310

NETWORK DIAGRAM



TECHNICAL SPECIFICATIONS

INTERFACE

- + PCI Express x1
- + 2 downstream USB type A (female) ports

STANDARDS

- + USB specification version 3.0
- + USB specification version 2.0
- + USB specification version 1.1 1
- + USB specification version 1.0
- + OHCI (open Host Controller Interface)
- + EHCI (Enhanced Host Controller Interface)
- + PCI Express 2.0

DATA RATES

- + SuperSpeed: 4.8 Gbps
- + High Speed: 480 Mbps
- + Full Speed: 12 Mbps
- + Low Speed: 1.5 Mbps

CONNECTIVITY

+ Up to 127 devices by cascading multiple hubs

SUPPLIED POWER

+ Maximum 900 mA per port

DIMENSIONS (L X W X H)

+ 2.98" x 2.42" x 0.72" (75.8 x 61.5 x 18.3mm)

WEIGHT

+ 0.09 lb (43 grams)

OPERATING TEMPERATURE

+ 32 to 104 °F (0 to 40 °C)

STORAGE TEMPERATURE

+ -4 to 140 °F (-20 to 60 °C)

OPERATING HUMIDITY


+0% to 80% (non-condensing)

CERTIFICATIONS

- + USB-IF
- + WHQL
- + FCC + CE

WARRANTY

1-Year Limited³



2 Using a USB 1.1 or USB 2.0 port will affect device performance.
3 - Year Limited Warranty available only in the USA and Canada.
4 Latest Software and Documentation available at http://support.dlink.com.
5 Computer must adhere to Microsoft's recommended system requirements.

Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted on the package. See inside package for warranty details

©2011 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo and the D-Link RoHS logo are registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners.



MINIMUM SYSTEM REQUIREMENTS

- - Windows[®] 7; WindowsVista[®], Windows XP SP3*or higher Available PCI Express slot Available 4-pin 12V peripheral power connector

PACKAGE CONTENTS

- + D-Link 2-Port USB 3.0 PCI Express Card (DUB-1310) + Low-Profile Bracket + CD Rom⁴

- Drivers User Manua

