



**DUB-A2**

- Two Hi-Speed USB 2.0 Ports
- Hi-Speed 480Mbps<sup>1</sup> Transfer Speeds
- Plug-&-Play
- Backwards Compatible with USB 1.1
- Compatible with Microsoft<sup>®</sup> Windows<sup>®</sup> XP, Me, 2000 and 98

## **QuickMedia** USB Solutions *Hi-Speed USB 2.0* **2-Port PCI Adapter**

The DUB-A2 is a Hi-Speed 2-Port USB 2.0 PCI adapter that upgrades desktop computers to the new and faster USB standard. This card is designed to work with mice, keyboards, external CD-R/RWs, external hard drives, PC cameras, and all other USB enabled devices. It is 40 times faster than previous USB adapters and 20% faster than Firewire (IEEE-1394). Each of the two USB 2.0 ports transfers data at 480Mbps<sup>1</sup>, making it ideal for external storage, backup, networking and digital video.

The DUB-A2 is certified to USB 2.0 standards and is backward compatible with USB 1.0 and USB 1.1

products. This gives you the ability to connect and operate all of your USB 1.x devices to the DUB-A2 USB 2.0 adapter and they will work. Each port detects whether the connected device is USB 1.x or USB 2.0 and automatically runs the device at the correct speed.

The DUB-A2 supports Plug-&-Play so once its installed inside your desktop PC, your operating system will automatically detect it, allowing you to start connecting your other USB devices immediately.

<sup>1</sup> Maximum transfer rate based on USB 2.0 specifications. Actual data throughput will vary.



# QuickMedia USB Solutions

## 2-Port USB 2.0

# PCI Adapter

### SPECIFICATIONS

#### Standards

- USB Specification Version 2.0
- USB Specification Version 1.1
- USB Specification Version 1.0
- OHCI 1.1 (Open Host Controller Interface)
- EHCI .95 (Enhanced Host Controller Interface)

#### Compatible Operating Systems

##### USB 2.0 Speed

- Microsoft® Windows® XP, ME, 2000, 98 with USB 2.0 Support

##### USB 1.x Speed

- Mac OS 8.6 to 9 with USB 1.x Support and USB Card Support 1.4.1
- Microsoft® Windows® XP, Me, 2000, 98 with USB 1.x Support

#### Ports

- Two downstream USB Type "A" receptacles

#### Connectivity

Up to 127 devices by cascading multiple hubs

#### Supplied Current

500mA per port

#### Certifications

USB-IF

#### Card Type

Supports PCI Version 2.2, 2.1 and 2.0

#### Operating Temperature

0°C to 40°C

#### Storage Temperature

0 to 95%, non-condensing

#### Humidity

5% to 95%, non-condensing

#### Compliances


CE, FCC Class B, VCCI, UL

#### Warranty

1 Year




DUB-A2



The DUB-A2 performs up to 40 times faster than USB 1.1 by utilizing the 480Mbps<sup>1</sup> throughput speed of Hi-Speed USB 2.0.

### Typical DUB-A2 Installation



<sup>1</sup> Maximum transfer rate based on USB 2.0 specifications. Actual data throughput will vary.



D-Link Systems, Inc. 17595 Mt. Hermann Fountain Valley CA92708-4160 www.dlink.com  
 ©Copyright D-Link Systems, Inc. 2003. All rights reserved. D-Link® is a registered trademark of D-Link Systems, Inc.  
 Other trademarks or registered trademarks are the property of their respective manufacturers or owners. Price and specifications are subject to changes without notice. See inside package for warranty details.

\* 24/7 Tech Support is available only in USA.

**D-Link®**  
 Building Networks for People